


Recessed LED Downlight IP20

LED Downlight-COB 20W

Model No.: SL-DL612020

Version: V1.0

Date: June 8th,2022



Features

- Family Design Total 4 Different Sizes With Wattage From 8W To 30W.
- Sand White Or Sand Black Color Lamp Body Surface Treatment.
- Interchangeable Secondary Reflector Finish Chrome Or Darken Nickel.
- High Transmittance Optic Lens, Optical Flexibility 15/24/36/60 Degree Beam Angle
- High Quality Aluminum Heat Sink With Excellent Thermal Dissipation.
- Ra90 High Color Rendering Is More Realistic, Restores The True Color Of The Subject.
- CCT Range 2700K/3000K/3500K/4000K/5000K/5500K .
- Constant Current Driver Output With Flicker Free, Led Driver Efficiency 85-90% .
- Supporting To Triac Dimming, 0/1-10V And DALI Dimming .
- 3 Years Warranty.

Application:

Widely Used In Commercial Lighting and Residential Lighting .Lighting Projects Like Hotels, Restaurants, Shopping Mall, Offices, Super markets.etc.

Luminaire Specification

| | |
|--------------------|-----------|
| Height | H 63.5 mm |
| Bezel | Ø 133 mm |
| Hole cut-out | Ø 120 mm |
| Luminaire material | Aluminium |
| IP Rating | IP20 |

LED Specification

| | |
|---------------|--------------------------------|
| LED | COB CREE |
| Power | 20W |
| CRI | Ra90 |
| CCT | 2700K, 3000K,3500K,4000K,5000K |
| Lumen | 1700lm |
| Beam angle | 15°/24°/36°/60° |
| Drive current | DC500mA,36V |
| Input voltage | AC220~240V/50-60Hz |
| Accessories | Honeycomb |

Ordering Information

| Beam angle | LED driver brand | LED CCT | Driver type | Power |
|--------------|------------------|---------|-----------------------|-------|
| 1 Narrow 15° | 1 Lifud | 1 2700K | 1 Triac Dimming | A 20W |
| 2 Medium 24° | 2 Tridonic | 2 3000K | 2 0-10V Dimming | |
| 3 Wide 36° | 3 Euchips | 3 4000K | 3 DALI Dimming | |
| 4 Flood 60° | 4 Eaglerise | 4 5000K | 4 Regular Non-dimming | |